

**ICAO High Intensity 50 000 cd White + 2 000cd Red
LED Aviation Obstacle Light****Key features**

- Based on LED-technology
- 50 000 cd effective flashing white, 2 000cd flashing/steady red omnidirectional
- Stand alone unit with power supply, fault monitoring and day/night switch integrated
- Over 10 year continuous, maintenance free operating time
- Integrated GPS antenna for flash synchronisation as an option
- Fault monitoring is through alarm relay. Ethernet and RS-485 are available as options
- Easy to chain (Power and Master /Slave synchronisation)
- Stabilised light output
- No RF-radiations
- Dimmable down to 30% and 10% .
- Integrated infra-red (IR) light as an option
- Comes with five (5) years warranty

**Obelux HI-50KWD-230-A****Specifications met**

- ICAO International Standards and Recommended Practices: Aerodromes - Annex 14 Volume 1, 5th Edition, July 2009, Chapter 6, high-intensity Type B (2 units required).
- Finnish aviation authority, TraFi, regulations

Order code

HI-50KWD-230-A 230 VAC
(comes with horizontal mounting)

Optical characteristics

- 50 000 cd effective intensity @ day and twilight mode
- 2 000 cd effective intensity @ night mode
- Colour aviation red
- Horizontal radiation pattern 360°
- Vertical radiation pattern 3°

Options (factory-installed):

- OPT-GPS-50KWD-A** GPS synchronisation -including integrated antenna
- OPT-LAN-50KWD-A** Ethernet interface - remote control
- OPT-IR-50KWD-A** Infra-red (IR) light (wavelength at 855nm)
- Compatible with Night Vision Goggles

Electrical characteristics

- Nominal operating voltage 230 Vac, 50...60Hz
- Constant power input by active PFC
- Flash rates: 20, 40 and 60 fpm
- Power consumptions @ 40 fpm:
Day mode: 160 VA
Night mode: 30 VA
- Operating temperature range -40...+55 °C
- Storage temperature range -55...+70 °C
- LED supply current stabilised by constant current generator

Shipping details

Dimensions: 60cm x 40cm x 40cm
Weight: 32 kg



Mechanical characteristics

- Anodised marine grade aluminium body
- Glass cover
- Degree of protection IP65
- Height 428 mm, diameter 360 mm
- Mounting set horizontal
- Light unit weight less than 27 kg

Made in Finland

Technical information in this document is subject to change without notice. Copyright © Obelux Oy 2012

Mechanical dimensions:



Technical information in this document is subject to change without notice. Copyright © Obelux Oy 2012